Pnömatik Sıyırma Makinası
Pneumatic Stripping Machine



AM.STRIP.015

Pnömatik soyma makinesi AM.STRIP.015, zor izolasyonların işlenmesi için özel olarak geliştirilmiştir. Standart V bıçaklarıyla, tüm kablo izolasyonları en iyi şekilde işlenebilir. Teflon, silikon, kynar, mylene, neoprene vb. gibi zor yalıtımların en iyi şekilde sıyrılması için özel yuvarlak ağızlı bıçaklar herhangi bir alet kullanılmaksızın saniyeler içinde takılabilir.

AM.STRIP.015, EC-Machinery Directive yönetmeliğine uygun şekilde gerekli tüm güvenlik ekipmanlarıyla donatılmıştır ve CE belgelidir

The pneumatic stripping machine AM.STRIP.015 has especially been developed for the processing of difficult isolation. With the V-blades used in the standard version, all usual cable isolations are processed optimally. Special die-blades can be fitted within seconds and without tools for optimal stripping at difficult isolations such as Teflon, silicone, kynar, mylene, neoprene etc.

Certainly, the AM.STRIP.015 is equipped with all necessary safety devices according to the EC-Machinery Directive.

be-ri®

FEINTECHNIK
R.Rittmeyer GmbH
Höltenweg 103
48 155 Münster
Germany

Telefon: +49 . (0)251.96115–0
Telefax: +49 . (0)251.624 525
E-mail: info@rittmeyer-beri.de
Web: www.rittmeyer-beri.de

Özel Nitelikler

- Son derece kısa bükülü tel uçları bile işlenebilir (Ko ruyucu kapak ile bıçaklar arası mesafe< = 9 mm!)
- Bıçaklara paralel hassas kablo kılavuzu
- Nozül, Düz ve Prizmatik sıyırma bıçaklarıyla işleme
- "Zipp & Klick" mekanizmamız sayesinde son derece hızlı bıçak değişimi
- Sıyırma işlemi için sensör tetiklemeli
- Kendi kendine merkezlenen sıkma çeneleri
- Bıçaklarda izolasyon artığı önleyici üfleme sistemi
- Uygun güvenlik kapağı
- Yukarıdan yerleştirmeli kablo yuvası
- Çekme kuvvetine bağlı olarak otomatik ayarlanan sıkma basıncı

Sıyırma Özellikleri


Yuvarlak kablolar:	5,0 mm dış çapa - ø kadar
Kablo kesiti:	0,15 – 4,0 mm²
Yassı kablolar:	8 mm genişliğe kadar
Tam sıyırma uzunluğu:	1,5 – 15 mm
Kısmi strok:	1 – 15 mm

Teknik Bilgiler


Çalışma Basıncı:	max. 3 – 6 bar
Hava / Çevrim(6 bar):	yakl. 0,15 lt
Çevrim süresi:	yakl. 0,5 sn.
Ağırlık:	yakl. 3,5 kg
G x D x Y:	95 x 280 x 165 mm

Değiştirilebilir Bıçaklar


Yuvarlak ağızlı, prizmatik ve düz sıyırma bıçakları



Yuvarlak Ağızlı Bıçak
die - blade



Prizmatik Bıçak
prismatic blade



Düz Bıçak
flat stripping blade

Special Characteristics

- extremely short stranded wire ends can be processed (distance cover to stripping blades < / = 9 mm!)
- exact parallel guide of the blades heads - processing with die – blades, prismatic blades and flat stripping blades
- blade change fast as lightning with our "zipp & click" change - System
- sensor release of the stripping process
- self – centring clamping jaws
- air blow – out (to avoid isolation rests)
- correct safety cover
- putting in the cable from above
- pressing power of the clamping jaws self-regulating (depending on the effecting removal power)

Stripping

round cables:	up to 5,0 mm outer - ø
cross section:	from 0,15 – 4,0 mm²
flat cables:	up to 8 mm width
stripping length:	1,5 – 15 mm
partial stroke:	from 1 – 15 mm

Technical Data

operating press:	max. 3 – 6 bar
air / cycle (6 bar):	ca. 0,15 l
cycle time:	ca. 0,5 sec.
weight:	ca. 3,5 kg
W x D x H:	95 x 280 x 165 mm

Insertable blades

Die-, prismatic or flat stripping blades